



Typical Floor Plan of A-30 EFP

SHOOK A-30 EFP SPECIFICATIONS

CHASSIS

GMC T-series 33,000 lb. [14,968 kg] GVWR with Air tag rear axle (Isuzu, Mercedes Benz, Mitsubishi, Nissan, and Volvo Chassis are available as an option)
 GMC 6.6 liter 275 HP CAT 3116 Electronic Diesel Engine
 GMC 9 Speed RT8609 Fuller Manual Transmission
 2 - 50 Gallon (189 Liter) Fuel Tanks
 Power Assisted Steering
 Air Brake System (Rockwell Q Series)
 Dual Maintenance Free Batteries (1500 Amp)
 Comprehensive Gauge Package with Voltmeter, Oil Pressure Temperature and Fuel Indicators
 100 Amp 12 Volt Alternator
 Front Cab Air Conditioning
 AM/FM Stereo Radio
 Underbody Undercoating (Petroleum Based)
 Laminated tinted glass
 2 side view stainless steel mirrors

AVAILABLE OPTIONS

Satellite Telephone
 5 Speed Allison HD Automatic Transmission
 Water Cooled Diesel Generator with Remote Start/Stop and Manual Shore power Changeover Switch
 Manually Controlled Hydraulic Stabilizing Jacks
 Custom Remote Controlled Electrically Operated Awnings
 Right Hand Drive Option (Mercedes Benz, Mitsubishi and Volvo)
 Logo from Customer Supplied Camera Ready Art work
 A Wide Choice of Custom Interior Color Schemes
 Custom Exterior Colors
 DC Operated Cable Reels
 30 - 42 - 48 - 52 - 56 - 58 Foot Pneumatic Telescoping Mast
 Multi Line Telephone system
 GPS Satellite System With Compass

HOUSING

.125 (3mm) Aluminum Skin Hard Bucked Riveted as Stainless Steel Low Maintenance Belly Boxes with Switched Interior Courtesy Lights, alarm switches and Ice Breaker latches.

Reinforced Interior Walls, Floor and Ceiling
 Sound Reducing Ceiling Treatment
 Industrial Grade Flame Retardant Tight Looped Anti-Static Carpet
 Non-flammable, Hard Packed Fiberglass Insulation
 Custom Built Equipment Racks with Operator Console
 Custom Heavy Duty .125 Aluminum Tread Plate Roof Platform
 Heavy Duty Rear Access Ladder
 Exterior Paint is GMC Multi-Coat OEM paint (White) Other Colors are Available at Additional Cost

Dual 30,000 BTU Air Conditioner with Shook Hot Gas Bypass Valve Modification. Includes 5KW (x2) heat strip
 UL® Approved Power Panel with Separate Circuit Breakers and Individual Power Strips in each rack
 AC Wiring run in Seal-Tight steel reinforced Flexible Conduit
 (1) Carbon Monoxide Detector (AC Operated) with generator
 25 KVA Isolation Transformer for Shore Power with Taps for 190/208/220/230 VAC

Digital Voltage/Amp Metering
 (1) Duplex Maintenance Outlet located on the Curb Side
 30 Amp DC Converter with 40 Amp Battery Charger and Battery Condition Metering.
 Custom Engraved, Locking External I/O Video/Audio Panel with Light
 (4) Waterproof DC Outside Work Lights. 2 - Located on Curb side and 2 - on Street side of the vehicle
 Interior Dimmable Operating Lights as Required
 Interior 12 V DC Courtesy Ceiling Light
 Removable Commercial Grade Swivel Chairs with Tie Down
 Remote Controlled Burglar Alarm System on All Access Doors

Visit Our Web Site: www.shook-usa.com

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE