



AS-15 SNG SPECIFICATIONS

THE CHASSIS

GMC C-series 25,950lb. [1175kg] GVWR (No CDL Required)
 Caterpillar or Cummins >210 HP Turbo diesel engine
 6 speed Fuller manual Transmission
 Two 35 gallon [132 liter] fuel tanks with feed to the generator
 Heavy duty cooling system
 Power steering and brakes
 Heavy duty front shock absorbers
 Dual maintenance free batteries (1500 CCA)
 100 amp, 12 volt alternator
 Comprehensive Gauge Package
 Front Cab Air Conditioning (CFC Free)
 AM/FM Stereo Radio with Clock
 Underbody Undercoating (Petroleum Based)
 Tinted glass
 Tow Hooks

SAFETY EQUIPMENT

ICC First Aid Kit
 Fire Extinguisher ABC Type
 CO Detector AC Powered with Battery Backup
 Backup Alarm
 Remote Controlled Burglar Alarm System

AVAILABLE OPTIONS

1.5, 1.8 or 2.4m low profile Satellite Antenna with GPS Controller
 Monochrome Back-up Camera
 Logo from Customer Supplied Art work
 Custom Exterior Colors
 Multi Line Telephone System
 Curb Side Side Awning
 Pneumatic Mast System 30, 42, 48, 52, 56 foot with Pan & Tilt
 RF Field and Proximity Detector System For Mast
 Mast Camera System with 10X Zoom Lens
 Antenna Up, Mast Up, Jacks Down Warning System

THE HOUSING

Reinforced Interior Walls, Floor and Ceiling
 Sonex™ or equal Sound Reducing Ceiling Treatment
 Industrial Grade Tight Looped Anti-Static Carpet
 Nonflammable, Hard Packed Insulation
 Custom Built Equipment Racks with Operator Console
 Custom Heavy Duty .125 Aluminum Tread Plate Roof
 Exterior Paint is OEM paint (White)
 (1) 30,000 Btu air conditioner/heater with Shook Hot Gas By-Pass mounted on front wall of housing. The Shook hot gas by-pass eliminates loading as a result of a locked rotor compressor start up during operation.
 UL" Approved Power Panel with Separate Circuit Breakers and Individual Power Strips in each rack
 20 kW 60Hz Diesel Generator mounted in a sound reducing compartment at the rear of the vehicle.
 Remote Start/Stop and Manual Changeover switch
 20 KVA Isolation Transformer for Shore Power with a capacity of 220 volt center tap, 150 amp single phase, primary taps for 190/208/220/230 VAC (Optional taps for European power are available)
 Digital Voltage/Amperage Metering
 Weatherproof AC duplex outlet located on the curb side of the vehicle
 25 Feet #6-3 with Ground Type "SO" Cable with Inlet Connector
 30 Amp DC Converter with 40 Amp Battery Charger
 Custom Engraved External I/O video/Audio Panel with Light
 (4) DC sealed beam exterior work lights-2 on each side of the vehicle
 One light directed at the face of the satellite antenna system for safety during deployment and stowage
 Interior 12V DC Ceiling Lights
 (1) DC Ceiling Light in Rear-Storage Compartment
 Removable Swivel Chairs with Tie Down (See plan for quantity and location)

Web: www.shook-usa.com - E-mail: shook@shook-usa.com - Toll Free: 1-888-651-5775

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE